



# MATERIAL SAFETY DATA SHEET

Revision 1  
Prepared 2006-11-27

## Section 1 - Chemical Product and Company Information

Product Name: WETSUIT ROOFING & WATERPROOFING COATING    Product Code: 17-WS-55

TradeName(s): WetSuit Roofing & Waterproofing Coating


Supplied by: Neptune Coatings Corporation  
972 Golden Gate Terrace  
Grass Valley, CA 95945

Emergency Contact:  
Neptune Coatings 1-800-967-7659

## Section 2 - Composition / Information on Ingredients

Chemical Name / CAS No	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
------------------------	----------------------	-----------------------	-----------------------

## Section 3 - Hazards Identification



HMIS Rating:    2 - 1 - 0

**Route of Entry:** Inhalation, Skin Contact, Eye Contact, Ingestion

**target Organs:** Respiratory System, Central Nervous System, Gastro-Intestinal Tract, Lungs, Cardiovascular System, Kidneys, Liver.

**Acute Toxicity:**

**Eyes:** Contact may cause irritation with tearing, pain, blurring of vision, corneal opacity or clouding of the eye. Avoid eye contact!

**Skin Contact:** Prolonged skin contact may cause redness and itching. In very severe exposures, blisters may occur.

**Effects of Overexposure, :**

**Skin Contact:** Prolonged skin contact may cause redness and itching. In severe exposure cases, blisters may occur.

**Ingestion:** Ingestion is not a probable route of exposure. The product is alkaline. Casutic products have been shown to effect the central nervous system and cause stomach distress.

**Inhalation:** At normal temperatures low exposures will be encountered. These vapors may be irritatating to the eyes, nose or throat. At high temperatures, above 200F vapors are irritating to the eye, nose and throat. Take precautions to avoid exposure.

**Eye:** Contact may cause irritation with tearing, pain, blurring of vision, corneal opacity or clouding of the eye. Avoid eye contact!

## Section 4 - First Aid Measures

**INHALATION:** Inhalation of mists may cause mild respiratory irritation. Remove from the exposure and provide with plenty of fresh air.

**EYE:**Liquid splashed in the eye may cause transient eye irritation. Flush immediately with large amounts of water for at least 15 minutes lifting the upper and lower eye lids occasionally. Take to a physician for medical treatment.

**SKIN CONTACT:** Short term exposure may cause transient skin irritation. Remove with soap and water and flush with copious amounts of water to the exposed areas to rinse the material away. If clothing was contaminated, remove and clean before reuse.

**INGESTION:** If ingested, consult a physician, hospital emergency room or poision control center immediately. (Never induce vomiting or give an unconcious person anything by mouth.)

**PHYSICIANS:** Any Treatment that might be required for overexposure should be directed at the symptoms and the clinical conditions.

## Section 5 - Fire Fighting Measures

Flash Point: None

LEL: N/A %

UEL: N/A %

This is a waterborne product with trace quantities of organic vapors. No ignition is will occur until the water is evaporated.

**CAUTION:** If closed containers are exposed to extreme heat, they may explode due to high steam pressure buildup.

**COMBUSTION PRODUCTS:** Carbon monoxide and carbon dioxide are the largest portion of products of combustion.

There will be hazardous gases of hydrogen chloride (HCl), other organic acids, and aldehides as well.

When water is used Fog nozzles are preferrable. Use water to cool closed containers.

Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH- approved or equivalent) and full protective gear.

## Section 6 - Accidental Release Measures

In the advent of a spill, contact the proper authorities as required.

Small spills should be confined with inert absorbent. Collect in a proper container for disposal. Dispose of in accordance with local regulations.

Do no allow large spills to get into any waterway, dry creek, sewer or water supply. Pump into proper drums for disposal.

Do not put contaminated paint into unused paint. Dispose of in accordance with local regulations.

## Section 7 - Handling and Storage

Store in a cool dry area. Temperatures of storage should be between 50 and 90 degrees Farenheitd.

PROTECT FROM FREEZING.

## Section 8 - Exposure Controls / Personal Protection

In most cases application of roof coating, ventilation is expected to be adequate. However if applied in confined areas, assure adequate ventilation through the use of fans, blowers etc.

When spraying, use an appropriate, properly fitted NIOSH/MSHA approved respirator to protect against spray mist and vapors. Refer to OSHA 29 CFR 1910.134 titled "Respiratory Protection" for further suggestions. Use a face shield or goggles with side shields for eye protection.

The use of nitrile rubber gloves and eye protection, safety glasses with side shields, is recommended. .

As a precautionary measure, It is recommended that a supply of clean water be available for an eye wash. Contaminated clothing and rags should be handled in compliance with local regulations. Contaminated clothing should be cleaned before reuse.

## Section 9 - Physical and Chemical Properties

This material exhibits the following properties under usual circumstances.

Appearance	Brownish to Black Opaque Material
Odor	Mild
Physical State	Liquid
Vapor Density	Heavier than air
Evaporation Rate	Like water
Specific Gravity (SG)	1.024
% Volume Solids	54.27

## Section 10 - Stability and Reactivity

STABILITY: This material is stable when stored at common room temperature and use conditions.

PROTECT FROM FREEZING.

INCOMPATIBILITY:None known

The following materials will likely be present as products of combustion: Carbon monoxide, carbon dioxide, hydrogen chloride, organic acids and aldehydes.

## Section 11 - Toxicological Information

### EXPOSURE LIMITS:

Oil Mist

OSHA PEL: 5 mg/m<sup>3</sup>

ACGIH TLV: 5 mg/m<sup>3</sup>

Sodium Hydroxide (NaOH)

OSHA PEL: 2 mg/m<sup>3</sup>

ACGIH TLV: 2 mg/m<sup>3</sup>

Potassium Hydroxide (KOH)

OSHA PEL: None Established

ACGIH TLV 2 mg/m<sup>3</sup>

## Section 12 - Ecological Information

Report Spills as required to the proper authorities. This material should be treated as an oil under DOT regulations. Avoid contact with waterways, dry creeks, any water supply or sewers.

## Section 13 - Disposal Considerations

ALWAYS DISPOSE OF ANY LIQUID OR DRY MATERIAL IN ACCORDANCE WITH LOCAL REGULATIONS.

**LIQUID WASTE:** Package and label properly for disposal. Take all paint that cannot be used to approved recycle centers, paint roundups, or county facilities that are approved collection sites. Contact county, city or state health services or fire departments to find the nearest recycle center. Do NOT dispose of in water steams or sewers.

**SOLID WASTE:** In many areas, dried paint may be disposed of into regular trash containers. Check with your local authorities before disposal.

**Section 14 - Transport Information**

DOT: This product is a water borne product with a flash point over 212 deg F (100 Deg C). It is classified as Non-Combustible and Non-Hazardous.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>HazardClass</u>
DOT	Roofing Coating, Non Hazardous	N/A	55	N/a

**Section 15 - Regulatory Information**

**TSCA Inventory Status:** All materials are in compliance with TSCA requirements for commercial use.

**State Right To Know:**

This product contains no known hazardous materials in excess of 1% (or 0.1% for Carcinogens). PA, MA, NJ

**California Proposition 65:** WARNING: This material does contain materials known to the State of California to cause cancer or other reproductive harm: Bitumens, Present at low concentrations (trace quantities) are Asphalt fumes, Chloroprene, butadiene and toluene.

**Clean Water Act/Oil Pollution Act**

This product may be classified as an oil under Section 311 of the Clean Water Act and under the Oil Pollution Act. Discharges or Spills must be reported to the National Response Center (1-800-424-8802).

**Section 16 - Other Information**

**DISCLAIMER:** The information in this document is based on the information received from supplier sources and the experience of Neptune Coatings. No representation or warranty is made by Neptune as to the accuracy or completeness of the information. Neptune makes no warranty, express or implied as to the useability of the product.