



MATERIAL SAFETY DATA SHEET

Revision 1
Prepared 2006-11-27

Section 1 - Chemical Product and Company Information

Product Name: WETSUIT ROOFING & WATERPROOFING COATING ACCELERATOR Product Code: 17-WS-AC

TradeName(s): WetSuit Roofing & Waterproofing Coating Accelerator

Supplied by: Neptune Coatings Corporation
972 Golden Gate Terrace
Grass Valley, CA 95945

Emergency Contact:


Neptune Coatings 1-800-967-7659

Section 2 - Composition / Information on Ingredients

Chemical Name / CAS No	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
------------------------	----------------------	-----------------------	-----------------------

Section 3 - Hazards Identification

WARNING: HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO THE SKIN, EYES AND RESPIRATORY TRACT.



HMIS Rating: 1 - 0 - 0

Route of Entry: Inhalation, Skin Contact, Eye Contact, Ingestion

target Organs: Respiratory System, Gastro-Intestinal Tract, Throat, and Lungs.

Acute Toxicity:

Eyes: Contact may cause irritation with tearing, pain, or blurring of vision. Avoid eye contact!

Skin Contact: Skin contact will cause irritation. Redness, itching and pain may result.

Inhalation: Causes irritation to the respiratory tract. Symptoms may include coughing and shortness of breath.

Ingestion: This is an acidic product. If ingested, severe burns of the mouth, throat and digestive system may result. Symptoms may include vomiting, stomach pain, increased pulse rate without blood pressure decrease and other gastrointestinal disturbances.

Effects of Overexposure, :

Skin Contact: Skin contact may cause redness, itching, and in severe cases, blisters.

Ingestion: Ingestion is not a probable route of exposure. If ingested, severe burns of the mouth, throat and digestive system may result. Symptoms may include vomiting, stomach pain, increased pulse rate without blood pressure decrease and other gastrointestinal disturbances.

Inhalation: At normal temperatures low exposures will be encountered. These vapors may be irritating to the eyes, nose or throat. Take precautions to avoid prolonged exposures.

Eye: Contact may cause irritation with tearing, pain, and blurring of vision. Avoid eye contact!

Section 4 - First Aid Measures

INHALATION: Inhalation of mists may cause respiratory irritation. Remove from the exposure and provide with plenty of fresh air. If breathing is difficult, give oxygen. Keep the person calm and warm and call a physician.

EYE: Liquid splashed in the eye may cause eye irritation. Flush immediately with large amounts of water for at least 15 minutes lifting the upper and lower eye lids occasionally. Take to a physician for medical treatment.

SKIN CONTACT: Short term exposure may cause skin irritation, dryness of the skin, or dermatitis. Remove with soap and water and flush with copious amounts of water to the exposed areas to rinse the material away. If clothing was contaminated, remove and clean before reuse.

INGESTION: If ingested and the person is conscious induce vomiting. Consult a physician, hospital emergency room or poison control center immediately. (Never induce vomiting or give an unconscious person anything by mouth.)

PHYSICIANS: Any Treatment that might be required for overexposure should be directed at the symptoms and the clinical conditions.

Section 5 - Fire Fighting Measures

Flash Point: None

LEL: N/A %

UEL: N/A %

This is a waterborne product. No ignition will occur until the water is evaporated.

CAUTION: If closed containers are exposed to extreme heat, they may explode due to high steam pressure buildup.

COMBUSTION PRODUCTS: Once the water is driven off, metal oxides may be present and acidic compounds.

Fight fires with water, carbon dioxide or dry chemicals. When water is used Fog nozzles are preferable. Use water to cool closed containers.

Wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH- approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

In case of a spill, contact the proper authorities as required.

Small spills should be confined with inert absorbent. Collect in a proper container for disposal. Dispose of in accordance with local regulations.

Do not allow large spills to get into any waterway, dry creek, sewer or water supply. Pump into proper drums for disposal. Dispose of in accordance with local regulations.

Section 7 - Handling and Storage

Store in a cool dry area. Temperatures of storage should be between 50 and 90 degrees Fahrenheit.

PROTECT FROM FREEZING.

This product is acidic. Store only in plastic, glass or Stainless Steel.

Section 8 - Exposure Controls / Personal Protection

This product is used as a part of a roof coating. In most cases when applying roof coatings, ventilation is expected to be adequate. However if applied in confined areas, assure adequate ventilation through the use of fans, blowers etc.

This product is a portion of a roof coating.

When spraying the coating, use an appropriate, properly fitted NIOSH/MSHA approved respirator to protect against spray mist and vapors. Refer to OSHA 29 CFR 1910.134 titled "Respiratory Protection" for further suggestions. Use a face shield and/or goggles with side shields for eye protection.

The use of nitrile rubber gloves and eye protection, safety glasses with side shields, is recommended. .

As a precautionary measure, It is recommended that a supply of clean water be available for an eye wash. Contaminated clothing and rags should be handled in compliance with local regulations. Contaminated clothing should be removed and cleaned before reuse.

Section 9 - Physical and Chemical Properties

This material exhibits the following properties under usual circumstances.

Appearance	Clear to light orange solution
Odor	Mild
Physical State	Liquid
Vapor Density	Heavier than air
Evaporation Rate	Like water
Specific Gravity (SG)	1.086
% Volume Solids	8.87

Section 10 - Stability and Reactivity

STABILITY: This material is stable when stored at common room temperature and use conditions.

PROTECT FROM FREEZING.

INCOMPATIBILITY: Lead, Calcium, Strontium salts, borax, alkali carbonates and hydroxides, silver protein and tannins.

The following materials will likely be present as products of combustion: Metal oxides and a variety of acidic products.

Section 11 - Toxicological Information

N/A

Section 12 - Ecological Information

Report Spills as required to the proper authorities. Avoid contact with waterways, dry creeks, any water supply or sewers.

This material is expected to be toxic to aquatic life.

Section 13 - Disposal Considerations

ALWAYS DISPOSE OF ANY LIQUID OR DRY MATERIAL IN ACCORDANCE WITH LOCAL REGULATIONS.

LIQUID WASTE: Package and label properly for disposal. Take product that cannot be used to approved recycle centers, paint roundups, or county facilities that are approved collection sites. Contact county, city or state health services or fire departments to find the nearest recycle center. Do NOT dispose of in water streams or sewers.

Section 14 - Transport Information

DOT: This product is a water borne product with a flash point over 212 deg F (100 Deg C). It is classified as Non-Combustible and Non-Hazardous for shipment.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>HazardClass</u>
DOT	Roofing Paint Accelerator, Non Hazardous	N/A	N/A	55

Section 15 - Regulatory Information

TSCA Inventory Status: All materials are in compliance with TSCA requirements for commercial use.

State Right To Know:

This product contains no known hazardous materials in excess of 1% (or 0.1% for Carcinogens). PA, MA, NJ

California Proposition 65: None known.

Section 16 - Other Information

DISCLAIMER: The information in this document is based on the information received from supplier sources and the experience of Neptune Coatings. No representation or warranty is made by Neptune as to the accuracy or completeness of the information. Neptune makes no warranty, express or implied as to the useability of the product.