

## Section 1 - Chemical Product and Company Information

Product Name: WETSUIT ROOFING & WATERPROOFING COATING ACCELERATOR Product Code: 17-WS-AC

TradeName(s): WetSuit Roofing & Waterproofing Coating Accelerator

Supplied by: Neptune Coatings Corporation  
972 Golden Gate Terrace  
Grass Valley, CA 95945


Emergency Contact:  
Neptune Coatings 1-800-967-7659

## Section 2 - Composition / Information on Ingredients

Chemical Name / CAS No	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
------------------------	----------------------	-----------------------	-----------------------

## Section 3 - Hazards Identification

WARNING: HARMFUL IF SWALLOWED OR INHALED. CAUSES IRRITATION TO THE SKIN, EYES AND RESPIRATORY TRACT.



HMIS Rating: 1 - 0 - 0

### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** liquid, transparent

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:**

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:** Mild Eye Irritation: Signs/symptoms may include redness, pain and tearing

**Skin Contact:** Mild Skin Irritation: Signs/symptoms may include localized redness, swelling and itching

**Inhalation:** Upper Respiratory Tract Irritation: Signs/symptoms include cough, sneezing, nasal discharge, headache, hoarseness and nose and throat pain

**Ingestion:** Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhoea, and vomiting

## Section 4 - First Aid Measures

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that the appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

## Section 5 - Fire Fighting Measures

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	No Data Available
Flash Point	Not Applicable
Flammable Limits - LEL	Not Applicable
Flammable Limits - UEL	Not Applicable

### 5.2 EXTINGUISHING MEDIA

Material will not burn

### 5.2 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedure:** Wear full protective equipment (Bunker Gear) and self-contained breathing apparatus (SCBA)

**Unusual Fire and Explosion Hazards:** Not applicable.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## Section 6 - Accidental Release Measures

In case of a spill, contact the proper authorities as required.

Small spills should be confined with inert absorbent. Collect in a proper container for disposal. Dispose of in accordance with local regulations.

Do not allow large spills to get into any waterway, dry creek, sewer or water supply. Pump into proper drums for disposal. Dispose of in accordance with local regulations.

## Section 7 - Handling and Storage

Store in a cool dry area. Temperatures of storage should be between 50 and 90 degrees Fahrenheit.

PROTECT FROM FREEZING.

This product is acidic. Store only in plastic, glass or Stainless Steel.

## Section 8 - Exposure Controls / Personal Protection

This product is used as a part of a roof coating. In most cases when applying roof coatings, ventilation is expected to be adequate. However if applied in confined areas, assure adequate ventilation through the use of fans, blowers etc.

This product is a portion of a roof coating.

When spraying the coating, use an appropriate, properly fitted NIOSH/MSHA approved respirator to protect against spray mist and vapors. Refer to OSHA 29 CFR 1910.134 titled "Respiratory Protection" for further suggestions. Use a face shield and/or goggles with side shields for eye protection.

The use of nitrile rubber gloves and eye protection, safety glasses with side shields, is recommended. .

As a precautionary measure, It is recommended that a supply of clean water be available for an eye wash. Contaminated clothing and rags should be handled in compliance with local regulations. Contaminated clothing should be removed and cleaned before reuse.

## Section 9 - Physical and Chemical Properties

This material exhibits the following properties under usual circumstances.

Appearance	Clear to light orange solution
Odor	Mild
Physical State	Liquid
Vapor Density	Heavier than air
Evaporation Rate	Like water
Specific Gravity (SG)	1.086
% Volume Solids	8.87

## Section 10 - Stability and Reactivity

STABILITY: This material is stable when stored at common room temperature and use conditions.

PROTECT FROM FREEZING.

INCOMPATIBILITY: Lead, Calcium, Strontium salts, borax, alkalai carbonates and hydroxides, silver protein and tannins.

The following materials will likely be present as products of combustion: Metal oxides and a variety of acidic products.

## Section 11 - Toxicological Information

N/A

## Section 12 - Ecological Information

Report Spills as required to the proper authorities. Avoid contact with waterways, dry creeks, any water supply or sewers. This material is expected to be toxic to aquatic life.

## Section 13 - Disposal Considerations

ALWAYS DISPOSE OF ANY LIQUID OR DRY MATERIAL IN ACCORDANCE WITH LOCAL REGULATIONS.

LIQUID WASTE: Package and label properly for disposal. Take product that cannot be used to approved recycle centers, paint roundups, or county facilities that are approved collection sites. Contact county, city or state health services or fire departments to find the nearest recycle center. Do NOT dispose of in water steams or sewers.

## Section 14 - Transport Information

DOT: This product is a water borne product with a flash point over 212 deg F (100 Deg C). It is classified as Non-Combustible and Non-Hazardous for shipment.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>HazardClass</u>
DOT	Roofing Paint Accelerator, Non Hazardous	N/A	N/A	55

## Section 15 - Regulatory Information

**TSCA Inventory Status:** All materials are in compliance with TSCA requirements for commercial use.

**State Right To Know:**

This product contains no known hazardous materials in excess of 1% (or 0.1% for Carcinogens). PA, MA, NJ

**California Proposition 65:** None known.

## Section 16 - Other Information

DISCLAIMER: The information in this document is based on the information received from supplier sources and the experience of Neptune Coatings. No representation or warranty is made by Neptune as to the accuracy or completeness of the information. Neptune makes no warranty, express or implied as to the useability of the product.