



WetSuit® Trowel

WetSuit® Trowel is a high viscosity, water-based coating specifically designed as a roofing and waterproofing patch. Applied by trowel or brush, it is ideal for sealing leaky roof penetrations, ducting, flashings, cracks, joints and tears. WetSuit® Trowel is ideal on EPDM, TPO, asphalt, wood, metal, concrete and foam. Additionally, WetSuit® Trowel can be used as a waterproofing adhesive for setting tile and stone.

Technical Data

VISCOSITY	140 KU+
SOLIDS CONTENT	68% by Weight
COVERAGE	10 sq. ft. per gallon yields 125 dry mils
APPLICATION TEMPERATURE	34°F to 110°F, Do not allow to freeze
FLAMMABILITY	Class A fire rated, ASTM 108 Flame Spread & Exposure
COLOR	Black
ELONGATION	1550%
CURE TIME	2 hours @ 75°F and 60% humidity
ACCELERATED CURE TIME	Instant skinning
PACKAGING	1 and 5 gallon plastic containers
SHELF LIFE	1 year @ 50°F to 105°F
CLEAN UP	Liquid state: Use detergent and water Solid state: Use a citrus based cleaner or mineral spirits



Neptune Coatings Corporation
972 Golden Gate Terrace • Grass Valley, CA 95945
Toll free: 1.800.967.7659 • Ph: 530.274.1356 • Fax: 530.477.4316
info@neptunecoatingscorp.com • www.neptunecoatingscorp.com